

CASE *III*

RBX 2 SERIES ROUND BALERS



MODEL	RBX442	RBX452	RBX452 Silage	RBX462	RBX462 Silage	RBX552	RBX562		
Bale Size:									
Diameter, in. (mm)	30-48 (762-1219)	36-60 (915-1524)	36-60 (915-1524)	36-72 (915-1828)	36-72 (915-1828)	36-60 (915-1524)	36-72 (915-1828)		
Width, in. (mm)	46.5 (1182)	46.5 (1182)	46.5 (1182)	46.5 (1182)	46.5 (1182)	61.5 (1562)	61.5 (1562)		
Weight, lb. (kg)*	300-750 (136-340)	400-1200 (181-544)	550-1800 (249-816)	400-1900 (181-862)	550-2000 (249-907)	500-1750 (227-794)	500-2200 (227-998)		
Baler Dimensions and Weight:									
Overall length, in. (mm)	135 (3429)	176 (4470)	176 (4470)	188 (4775)	188 (4775)	176 (4470)	188 (4475)		
Overall width, in. (mm)	85 (2159)	94.5 (2400)	94.5 (2400)	94.5 (2400)	94.5 (2400)	111 (2819)	111 (2819)		
Overall height, in. (mm)	86 (2184)	104.8 (2662)	104.8 (2662)	114.3 (2903)	114.3 (2903)	102 (2580)	113.5 (2882)		
Weight, lb. (kg)	2950 (1338)	5050 (2290)	5100 (2312)	5900 (2676)	6310 (2862)	5525 (2506)	6095 (2765)		
Pickup:									
Overall width, in. (mm)	59.75 (1518)	76.5 (1943)	83.9 (2132)	76.5 (1943)	83.9 (2132)	88.3 (2243)	88.3 (2243)	Std width	Wide pickup
Width between side sheets, in. (mm)	52.6 (1336)	68.5 (1740)	79 (2013)	68.5 (1740)	79 (2013)	68.3 (1736)	68.3 (1736)	88.3 (2243)	94.4 (2399)
Width between outside tines, in. (mm)	44.6 (1133)	60.4 (1534)	71.1 (1805)	60.4 (1534)	71.1 (1805)	60.4 (1534)	60.4 (1534)	68.3 (1736)	90 (2280)
Tine spacing, in. (mm)	2.63 (67)	2.63 (67)	2.63 (67)	2.63 (67)	2.63 (67)	2.63 (67)	2.63 (67)	60.4 (1534)	81.6 (2072)
Number of tine bars	4	4	4	4	4	6	6	2.63 (67)	2.63 (67)
Number fo tines	72	96	112	96	112	144	144	6	4
Cam type	Single	Dual	Dual	Dual	Dual	Single	Single	144	128
Pickup tires	One - 4.8x4-8, 4PR	Two-16.5x6.5-8, 4 PR	Two-16.5x6.5-8, 4 PR	Two-16.5x6.5-8, 4 PR	Two-16.5x6.5-8, 4 PR	Two - 16.5x6.5-8, 4PR	Two - 16.5x6.5-8, 4PR	Single	Dual
Windguard	Adjustable/Pivoting/Floating	Adjustable/Pivoting/Floating	Adjustable/Pivoting/ Floating/Curved Tines	Adjustable/Pivoting/Floating	Adjustable/Pivoting/ Floating/Curved Tines	Adjustable/Pivoting/Floating	Adjustable/Pivoting/Floating	Two - 16.5x6.5-8, 4PR	Two (same both models)
Protection	Adjustable Slip Clutch	Adjustable ratchet clutch	Adjustable ratchet clutch	Adjustable ratchet clutch	Adjustable ratchet clutch	Adjustable ratchet clutch	Adjustable ratchet clutch	Adjustable/Pivoting/Floating	Adjustable/Pivoting/Floating (same both models)
Stuffer									
Type	—	One Segment	Two Segment	One Segment	Two Segment	—	—	—	Two Segment
Number of Fingers	—	16	16	16	16	—	—	—	22
Finger spacing, in. (mm)	—	2.6 (66)	2.6 (66)	2.6 (66)	2.6 (66)	—	—	—	2.6 (66)
Bale Wrapping:									
Type	1 pivoting arm applies 2 twines at once	Dual twine arms	Dual twine arms	Dual twine arms	Dual twine arms	Dual twine arms	Dual twine arms	Dual twine arms	Dual twine arms
Twine	4 balls	6 std., option 11 total	6 std., option 11 total	6 std., option 11 total	6 std., option 11 total	6 std., option 12 total	6 std., option 12 total	6 std., option 12 total	6 std., option 12 total
Mesh	—	—	2 rolls	—	2 rolls	—	2 rolls	—	2 rolls
Belts:									
Number	6	6	6	6	6	8	8	8	8
Width, in. (mm)	7 (178)	7 (178)	7 (178)	7 (178)	7 (178)	7 (178)	7 (178)	7 (178)	7 (178)
Length, in. (mm)	272.5 (6922)	343 (8712)	343 (8712)	420.5 (10681)	420.5 (10681)	343 (8712)	420.5 (10681)	420.5 (10681)	420.5 (10681)
Type	Laced, Chevron pattern, 3 ply	Laced, Chevron pattern, 3 ply	Endless, Chevron pattern, 3 ply	Laced, Chevron pattern, 3 ply	Endless, Chevron pattern, 3 ply	Laced, Chevron pattern, 3 ply	Laced, Chevron pattern, 3 ply	Laced, Chevron pattern, optional endless, 3 ply	Laced, Chevron pattern, optional endless, 3 ply
Tires:									
	11L x 14	31 x 13.5	31 x 13.5	31 x 13.5	31 x 13.5	14L - 16.1	14L - 16.1		
Tractor requirement:									
Minimum PTO Hp (kW)/PTO rpm	40 (30), 540	60 (45), 540	65 (48), 540	70(52), 540	75 (56), 540	70 (52), 540	80 (60), 540 or 1000		
Number of Hydraulic remotes required**	1	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2		

*Bale weight depends upon crop type and moisture content

**Depending on options

Case Corporation reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

SEE YOUR LOCAL CASE IH DEALER

This literature has been published for worldwide circulation. Availability of some models and equipment builds varies according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your Case IH dealer/distributor will be able to give you details of the products and their specifications available in your area.

WORLDWIDE CASE IH CONTACT INFORMATION

UNITED STATES/CANADA: 700 STATE STREET RACINE, WI 53404 USA

LATIN AMERICA: AV. JUSCELINO KUBITSCHEK DE OLIVEIRA N. 11825 CAIXA POSTAL 14040 CEP 81503 CURITIBA, PARANA, BRAZIL

WESTERN AND CENTRAL EUROPE/CIS: CRANES FARM ROAD BASILDON ESSEX SS143AD ENGLAND

EASTERN EUROPE/AFRICA/ASIA: VIALE DELLE NAZIONI 55 41100 MODENA, ITALY

AUSTRALIA/NEW ZEALAND: 31-67 KURRAJONG ROAD ST. MARYS NEW SOUTH WALES 2760 AUSTRALIA



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

